



WHY HANMIX?

HANMIX is an international brand with 40 years' experience in Tyre and Tyre Accessories business. HANMIX is not only a brand name, but a way for a better life. You can find security, safety and high quality life in the HANMIX World.

HANMIX THE QUALITY

HANMIX is committed to conducting comprehensive assessments of product quality, price, ability to supply our clients locally and internationally. All HANMIX products comply with international quality standards and are respected throughout the world.

-----WWW.HANMIX.NET

Quality Control:

HANMIX provides quality and quantity inspections, and offers a warranty for products purchased.



Inspected each tyre from production to the warehouse to the markets.
Inspected each tyre by serial number, tread depth and weight.
Inspected each tyre by international laboratory standards.




HP TIRE

Applicable Models



ECO 01



Product features:

Widened shoulder tread design increases contacting area, providing better driving stability and reliability.

Continuous straight center rib design provides optimized ground contact area, guarantees better driving safety.

Excellent grip and handling performance on wet land.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
175/70R12 WSW	80T	5J	511	177	450	250 250
185/60R13 WSW	80H	5½J	552	189	450	250 250
175/70R13	82T	5J	576	177	475	250 250
175/65R14	82H	5	584	177	475	250 250
175/70R14	84H	5J	602	177	500	250 250
175/70R14	84T 88T	5	602	177	500	280 280
185/70R14	91H	5.5	616	189	560	250 250
195/70R14	88H	6	630	201	615	250 250
185/65R15	91V	5.5	621	189	560	280 250
195/65R15	91V	6J	635	201	615	250 250
195/65R15	94V	6	635	201	615	290
205/65R15	98H	6	647	209	670	
215/65R15	96T	6½J	686	221	750	
205/70R15	100H	6	669	209	710	
225/70R15 WSW	91V	6½J	697	228	800	
205/55R16	91V	6½J	632	214	615	
205/55R16	95H	6.5	632	214	615	
215/60R16	95V	6.5	664	221	690	
215/60R16	95H	6½J	664	221	690	
205/65R16	98W XL	6J	672	209	690	
215/55R17		7J	668	226	750	

WINTER TIRE

Applicable Models




Product features:

Assisted groove design strengthens grip, drainage and braking performance. Center consecutive tread pattern design, ensure the stability of straight driving.

Lateral three-dimensional steel disc improves tread elasticity, enhances grip and safe handling performance on ice and snow road.

V-shape groove design improves excellent handling, dry/wet grip, drainage and snow performance.

The three-dimensional steel disc design in the shoulder improves friction between tread and ice road, meanwhile reduces noise. Thus better comfort and safety performance are provided.



SNOW FORCE

Size	Load Index	Speed	SW (mm)	OD (mm)
175/70R13	82	T	177	576
175/65R14	82	H	177	584
170/70R14	84	T	177	602
185/60R14	82	H	189	578
185/65R14	86	H	189	596
185/60R15	88XL	T	189	603
185/65R15	92XL	T	189	621

Size	Load Index	Speed	SW (mm)	OD (mm)
195/55R15	89XL	H	201	595
195/60R15	88	H	201	615
195/65R15	91	H	201	635
205/65R15	94	H	209	647
215/75R15	100	T	216	703
195/55R16	91XL	H	201	620
205/55R16	94XL	H	214	632


SNOW FORCE

Size	Load Index	Speed	SW (mm)	OD (mm)
205/60R16	96XL	H	209	652
215/55R16	97XL	V	226	642
215/60R16	99XL	H	221	664
215/65R16	102XL	H	221	686
215/70R16	100	T	221	708
235/60R16	104XL	H	240	688
235/70R16	109XL	T	240	736
205/50R17	93XL	V	214	638
215/50R17	95XL	V	226	648
225/50R17	98XL	V	233	658
215/55R17	98XL	V	226	668
215/60R17	100XL	H	221	690
225/45R17	94XL	V	225	634
225/55R17	101XL	V	233	680
225/60R17	99 102	H	228	702
225/65R17	97XL	H	228	724
235/45R17	103XL	V	236	644
235/55R17	108XL	V	245	690
235/65R17	112 95	H	240	738
265/65R17	92XL	H	272	776
215/55R18	95XL	V	226	693
225/40R18	99XL	V	230	637
225/45R18	98	V	225	659
225/50R18	104XL	V	233	683
225/55R18		V	233	705
225/60R18		H	228	727

RUN FLAT

No.	Size	LI/SS
1	225/40ZRF18	92V
2	225/45ZRF18	95V XL
3	235/50ZRF18	101V
4	235/55ZRF18	104V
5	245/40ZRF18	97V XL
6	245/45ZRF18	100V
7	245/50ZRF18	100V
8	255/40ZRF18	95V
9	255/55ZRF18	109V
10	225/45ZRF19	96V XL
11	235/55ZRF19	105V XL
12	245/45ZRF19	98V
13	245/50ZRF19	101V
14	255/50ZRF19	107V XL
15	275/40ZRF19	101V

HP TIRE



Product features:

Criss-cross grooves design enhance water evacuation, effectively prevent tire lateral slip on wet road.

Central rib combined with horizontal grooves provides nice stability, excellent acceleration and brake performance at high speed.



GRANDRANK HX01


Size	LI/S S	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
215/65R16		6½J	686	221	750	250 250
215/70R16	98H 100H	6½J	708	221	800	

HP TIRE

Applicable Models



GRANDRANK HX02



Product features:

Four wide grooves design provide effective drainage and sufficient wet safety performance.

Design of central rib with sipes promotes the rigidity, help to balance high-speed performance and grip performance on wet land.


The compact shoulder design provide excellent handling performance with low noise.

Multiple blade groove pattern provide excellent grip and handling performance on wet land.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
235/55R17	103V	7½J	690	245	290	290
225/65R17	106H	6½J	724	228	875 950	290 290
245/65R17	111H	7J	750	248	1090 900	250
235/55R18	104V	7½J	715	245	1180	
265/65R18	114H	8J	801	272		

UHP TIRE

Applicable Models



Product features:

Smooth asymmetric pattern, ensuring better controlling performance of outside while enhancing drainage of inside.

Four wide deep grooves keep excellent wetting performance and handling stability.

Outside shoulder reinforcement improving handling performance at curve, effectively preventing abnormal wear.

Bended steel groove, effectively reducing the noise while enlarging ground contact area.



GRANDRANK HX03


Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
225/60R17	103V	6½J	702	228	875	290 290
245/45R20	103W	8J	728	243	875	



GRANDRANK HX07

UHP TIRE

Applicable Models



Product features:


Asymmetric pattern design provides excellent grip on curves, ensuring stability during driving and offering excellent water drainage performance.

Optimized pitch width and arrangement and pitch displacement design effectively reduce noise during driving.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
215/50R17	91V	7	648	226	615	283 336
215/55ZR17	98W XL	7	668	226	750	338 336
225/50ZR17	98W XL	7	658	233	750	281 336
225/55ZR17	101W XL	7	680	233	825	336 302
235/55R17	99V	7.5	690	245	775	338 336
225/45ZR18	95W XL	7.5	659	225	690	
245/45ZR18	100W XL	8	667	243	800	
245/45ZR19	98W	8	703	243	750	
255/45ZR19	104W XL	8	713	255	900	
245/45ZR20	103W XL	8	728	243	875	

LTR TIRE

Applicable Models



Product features:

SIPS: The small, slit-like grooves in tread blocks that allow the blocks to move. This added flexibility increases traction by creating an additional biting edge. Sipes are especially helpful on ice, light snow, and loose dirt.

SHOULDER: Shoulders wrap slightly over the inner and outer sidewall of a tire and provide continuous contact with the road while maneuvering.

TREAD BLOCK: The segments making up a tire's tread. The primary function of tread blocks is to provide traction.



GRANDRANK LT2


Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
195R14C WSW	106/104	5½J	666	198	950/900	450 450
205R14C WSW	P	6J	686	208	1030/975	450 450
205/70R15C	109/107	6J	669	209	950/900	450
WSW	N	6½J	683	221	1030/975	
215/70R15C	106/104	6½J	697	228	1120/1060	
WSW	Q					
225/70R15C	109/107					
WSW	R					
	112/110R					

SUV TIRE

Applicable Models



GRANDRANK HX21



Product features:

Four wide grooves design provide effective drainage and sufficient wet safety performance.

The compact shoulder design provide excellent handling performance with low noise.


Design of central rib with sipes promotes the rigidity, help to balance high-speed performance and grip performance on wet land.

Multiple blade groove pattern provide excellent grip and handling performance on wet land.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
265/70R17	115T	8J	804	272	1215	250 250
265/60R18	110H	8J	775	272	1060	290
285/50R20	116V	9J	794	297	1250	

AT TIRE

Applicable Models  



Product features:

Prevent stone nipped, enhance the ability to get rid of the stone.

Solid staggered central rib design ensures straight-line driving stability and safety.

Enhance the block rigidity, endurance, weight-carrying ability and steering qualities during driving.

Promote the grip performance on wet and dry land, enhance the tractive performance.



GRANDRANK HX22

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
265/70R16	112T	8J	778	272	1120	250 250
275/70R16	114T	8J	792	279	1180	250 250
265/65R17	112T	8J	776	272	1120	290
285/65R17	116H	8½J	802	292	1250	
285/60R18	120H	8½J	799	292	1400	


XL

at TIRE

Applicable Models



GRANDRANK HX23



Product features:


- Aggressive all-terrain traction on and off-road.
- Robust sidewall design.
- Staggered shoulder blocks for greater maneuverability in soft soil.
- Advanced tread design for longer wear.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (lbs)	Pressure (psi)
215/75R15LT	100/97S	6.00J	701	216	1765/1610	50
235/75R15LT	104/101S	6.50J	734	236	1985/1820	50
31x10.50R15LT	109S	8.50J	775	269	2270	50
215/70R16LT	100/97R	6.50J	706	221	1765/1610	50
235/70R16LT	104/101S	7.00J	734	241	1985/1820	50
245/70R16LT	113/110S	7.00J	749	249	2535/2335	65
245/75R16LT	120/116S	7.00J	772	249	3042/2778	80
265/70R16LT	121/118S	8.00J	776	268	3195/2910	80
265/75R16LT	123/120R	7.50J	802	268	3415/3085	80
275/70R16LT	119/116S	8.00J	790	279	3000/2755	65
285/75R16LT	126/123R	8.00J	832	285	3750/3415	80
265/65R17LT	120/117S	8.00J	774	268	3085/2835	80
265/70R17LT	121/118S	8.00J	802	268	3195/2910	80
285/70R17LT	121/118R	8.50J	830	291	3195/2910	80
315/70R17LT	121/118S	9.50J	872	320	3195/2910	80
35x12.50R17LT	121R	10.00	876	318	3195	65
265/60R18LT	119/116S	J	775	272	3000/2755	80
275/65R18LT	123/120R	8.00J	813	279	3415/3085	80
285/65R18LT	125/122R	8.00J	826	292	3640/3305	80
265/70R18LT	124/121R	8.50J	828	272	3525/3195	80
285/50R20LT	119/116R	8.00J	798	298	2992/2750	80
275/60R20LT	119/116S	9.00J	836	279	3000/2755	80

8.00J

HP TIRE

Applicable Models  



Product features:

- Energy-saving and comfortable driving.
- Excellent the hydroplaning and wet performance.
- Good handling and comfort performance.
- Low noise and high tread wear.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
155/65R13	73T	4.50B	532	157	365	300 300
165/65R13	77T	5.00B	544	170	412	300 300
★	77T	5.00B	540	177	412	300 300
175/60R13	82T	5.00B	576	177	475	300 300
★	86T	5.50B	590	189	530	300 300
175/70R13	82H	5J	584	177	475	300 300
★	84T	5J	602	177	500	300 300
185/70R13	82H	5½J	578	189	475	300 300
175/65R14	86H	5½J	596	189	530	300 300
★	88T	5½J	616	189	560	300 300
175/70R14	86H	6J	590	201	530	300 300
★	91T	6J	630	201	615	300 300
185/60R14	88H	6J	602	209	560	
185/65R14	75H	5½J	557	182	387	
★	82H	6J	585	194	475	
185/70R14	88H	5½J	621	189	560	
195/60R14	85V/	6J	595	201	515	
★	H 88H	6J	615	201	560	
195/70R14	★	91H	6J	635	201	615
★	91H	6J	627	209	615	
205/60R14	91H	6J	627	209	615	
175/50R15	94H	6J	647	209	670	
185/55R15	91H	6½J	632	214	615	
★	92V	6J	652	209	630	
185/65R15	95V/	6½J	664	221	690	
195/55R15	H					




CLASSIC CL01

LTR TIRE

Applicable Models



CLASSIC CL02



Product features:

- Enhanced grip on off-road surface.
- Excellent water dispersion and hydroplaning resistance.
- Improved heat dissipation and grip performance.
- Quiet driving performance at high speed.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
155R12LT 6PR	83/81N	4.50B	553	157	487/462	350 350
155R12C 6PR	83/81N	4.50B	553	157	487/462	450 450
155R12LT 8PR	88/86N	4.50B	553	157	560/530	450 450
★ 155R12C	88/86N	4.50B	553	157	560/530	450 450
8PR 155R13LT	90/88N	4.50B	578	160	600/560	450 450
8PR 155R13C	90/88N	4.50B	578	160	600/560	450 450
8PR 165R13LT	94/93Q	4.50B	594	165	670/650	450 450
8PR 165R13C	94/93Q	4.50B	594	165	670/650	
8PR 165R14C	97/95Q	4½J	620	165	730/690	
8PR 165R14LT	97/95Q	4½J	620	165	730/690	
8PR 175R13LT	97/95Q	5.00B	610	177	730/690	
8PR ★	97/95Q	5.00B	610	177	730/690	
175R13C 8PR	99/98Q	5J	636	177	775/750	
175R14C 8PR	99/98Q	5J	636	177	775/750	
175R14LT 8PR						


CLASSIC CL02

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (Kg)	Inflated Pressure (Kpa)
185R14LT 8PR	102/100Q	5½J	652	189	850/800	450
★ 185R14C 8PR	102/100Q	5½J	652	189	850/800	450
195R14LT 8PR	105/103Q	5½J	668	196	925/875	450
★ 195R14C 8PR	106/104Q	5½J	668	196	950/900	450
205R14LT 8PR	107/105R	6J	684	208	975/925	450
205R14C 8PR	109/107R	6J	684	208	1030/975	450
215R14LT 8PR	110/108R	6J	700	218	1060/1000	450
215R14C 8PR	112/110R	6J	700	218	1120/1060	450
215/75R14LT 8PR	104/101Q	6J	678	216	900/825	450
215/75R14C 8PR	112/110Q	6J	678	216	1120/1060	475
185R15LT 8PR	103/102S	5½J	677	189	875/850	450
185R15C 8PR	103/102S	5½J	677	189	875/850	450
195R15LT 8PR	106/104Q	5½J	693	196	950/900	450
★ 195R15C 8PR	106/104Q	5½J	693	196	950/900	450
195/70R15LT 8PR	99/96R	6J	655	201	775/710	450
★ 195/70R15C 8PR	104/102R	6J	655	201	900/850	450
205/70R15C 8PR	106/104R	6J	669	209	950/900	450
215/70R15C	109/107R	6½J	683	221	1030/975	450
225/70R15LT 8PR	106/103R	6½J	697	228	950/875	450
225/70R15C 8PR	112/110R	6½J	697	228	1120/1060	450
215/75R16C 8PR	113/111R	6J	728	216	1150/1090	475
225/65R16C 8PR	112/110R	6½J	698	228	1120/1060	475
235/65R16C 8PR	115/113R	7J	712	240	1215/1150	475

at TIRE



CLASSIC CL03



Product features:

Improved grip and traction, sufficiently reduces braking distance under dry or wet.

Good ability to break water surface tension and reduces sliding on wet.


Great resistance to impact and load capability.

Low noise during driving.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
★ 205R16C 8PR	110/108R	6J	736	208	1060/1000	450 450
205R16LT 8PR	110/108R	6J	736	208	1060/1000	375 375
255/70R15C 6PR	112/110S	7½J	739	260	1120/1060	450 300
255/70R15LT 6PR	112/110S	7½J	739	260	1120/1060	300 300
★ 255/70R15C	113/110S	7½J	739	260	1150/1060	300 300
8PR	112T	8J	778	272	1120 1180	300 300
★ 265/70R16	114T	8J	792	279	1120 1215	
★ 275/70R16	112S	8J	776	272	1215 1060	
★ 265/65R17	115T	8J	790	279	1250	
275/65R17	115T	8J	804	272		
★ 265/70R17	110H	8J	775	272		
265/60R18	116T	8½J	799	292		

★ 285/60R18

LTR TIRE



Product features:

Good straight line stability and steering performance.
 Great loading capability.
 Good drainage and safty performance on wet road.
 More quite driving experience.



CLASSIC CL04


Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
7.50R16LT 8PR	114/112S	6.00G	805	215	1180/1120	475 560
★ 7.50R16LT 10PR	116/111S	6.00G	805	215	1250/1090	475
★ 225/95R16C	118/116Q	6J	834	223	1320	



CLASSIC CL05

LTR TIRE

Applicable Models




Product features:

Unique tread compound that offers superior cut and chip resistance. Long life and exceptional irregular wear resistance. Good load-bearing capacity.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
7.50R16C 8PR	114/112S	6.00G	805	215	1180	475

LTR TIRE

Applicable Models



Product features:

Excellent high speed road durability and stability.
Straight rib pattern ensures P_{rm} grip on soft sand.




CLASSIC CL06

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
225/95R16C 10PR	122/118Q	6J	834	223	1500	550 475
★ 225/95R16C 8PR	118/116Q	6J	834	223	1320	



CLASSIC CL07


SUV TIRE



Product features:

- Comfort, quiet and durability performance.
- Excellent the hydroplaning and wet performance.
- Good steering and stability at high speed.
- Excellent ride and low noise performance.
- Stiff tread and uniform wear.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
★ 265/65R18	114H	8J	801	272	1180	300 340
★ 285/50R20	116V XL	9J	794	297	1250	



UHP TIRE

Applicable Models  

Product features:

Excellent grip ensures the stability of straight and curved in wet terrain.

Strong block effectively enhances side cornering traction.

Rapid drainage performance in wet terrain.

Optimized pattern design reduce tire noise and improves vehicle safety.



CLASSIC CL08


Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
205/50R15	86V	6½J	587	214	530	300 300
205/55R15	88V	6½J	607	214	560	300 340
225/60R15	96V	6½J	651	228	710	300 300
195/55R16	91V XL	6J	620	201	615	300 300
195/60R16	89H	6J	640	201	580	340 300
★ 205/55R16	91V	6½J	632	214	615	300 300
205/60R16	92V	6J	652	209	630	300 340
★ 205/65R16	95H	6J	672	209	690	340 340
215/55ZR16	93W	7J	642	226	650	340 340
215/60R16	95V	6½J	664	221	690	340 340
★ 215/65R16	98H	6½J	686	221	750	300 340
225/60R16	98H	6½J	676	228	750	340
★ 235/60R16	100H	7J	688	240	800	
205/40ZR17	84W XL	7½J	596	212	500	
205/45ZR17	88W XL	7J	616	206	560	
215/45ZR17	91W XL	7J	626	213	615	
215/50ZR17	95W XL	7J	648	226	690	
★	98W XL	7J	668	226	750	
215/55ZR17	94W XL	7½J	634	225	670	
225/45ZR17	98W XL	7J	658	233	750	
★	97V	7J	680	233	730	
225/50ZR17	95W XL	7½J	659	225	690	
★ 225/55R17	100W XL	8J	677	243	800	
225/45ZR18						

SUV TIRE

Applicable Models



CLASSIC CL09



Product features:


Good straight, curved high-speed stability and wetland drainage performance.

Optimized pattern design enhances the lateral grip and improves vehicle safety. Low driving noise ensure a quieter driving environment.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
215/70R16	100H	6½J	708	221	800 950	300 300
235/70R16	106H	7J	736	240	1180 710	300 300
275/70R16	114H/T	8J	792	279	775 850	300 300
★	96H 99H	6½J	690	221	900 1120	300 300
215/60R17	102H	6½J	702	228	975	340
★	104H	6½J	724	228		
225/60R17	112H	7J	738	240		
★	107V	8J	776	272		
225/65R17	XL	7J	739	240		

★
235/65R17
265/65R17
235/60R18

SUV TIRE



Product features:

Good straight, curved high-speed stability and wetland drainage performance.

Optimized pattern design enhances the lateral grip and improves vehicle safety.

Low driving noise ensure a quieter driving environment.



CLASSIC CL10

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
225/70R16	103H	6½J	722	228	875 975	300 300
★	107H	7J	750	248	1120 975	300 300
245/70R16	112H/T	8J	778	272	1215 900	300 340
265/70R16	107H	7J	750	248	1060 750	300 300
245/65R17	115H/T	8J	804	272	800 925	300 300
265/70R17	104V XL	7½J	715	245		
★	110H	8J	775	272		
235/55R18	98V	7J	705	233		
265/60R18	100V	6½J	727	228		
225/55R18	105H	7J	751	248		
225/60R18						


★
245/60R18

HP TIRE

Applicable Models



CLASSIC CL11





Product features:

Good quietness brings stable and comfortable driving experience. Excellent handling performance can respond sensitively to various corners. Deep grooves and outstanding tread compound for endurance and long-lasting use.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
135/70R12	65	4.00B	495	138	290	250 250
145/70R12	Q	4.50B	509	150	325	300 300
145/80R12	69T	4.00B	537	145	375	300 300
175/70R12	74T	5.00B	551	177	450	300 300
★	80T	5.00B	562	170	437	300 300
165/70R13	79T	5.00B	576	177	475	
175/70R13	82T	5.50B	590	189	530	
185/70R13	86T	5½J	596	189	530	
★	86T	5½J	616	189	560	
185/65R14	88T	6J	644	209	690	
185/70R14	95T					
205/70R14						

HP TIRE

Applicable Models  



Product features:

Good steering performance and ride comfort.

Excellent hydroplaning and wet and sensitivity of high speed performance.



CLASSIC CL12

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
155/70R12	73T	4.50B	523	157	365	250 250
165/70R12	77T	5.00B	537	170	412	240 340
135/80R13	60L	4.00B	546	138	250	300 300
135/80R13	74N XL	4.00B	546	138	375	340 250
145/60R13	66N	4.50B	504	150	300	250 240
145/80R13	75T	4.00B	562	145	387	300 250
145/80R13	79N XL	4.00B	562	145	437	250
155/65R13	73T	4.50B	532	157	365	
155/70R13	75T	4.50B	548	157	387	
155/80R13	79T	4.50B	578	157	437	
165/55R13	70N	5.00B	512	170	335	
165/65R13	77T	5.00B	544	170	412	
165/70R13	79T	5.00B	562	170	437	


Good stability on dry ground, great response

CLASSIC CL12

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
165/70R13LT 6PR	88/86S	5.00B	562	170	560/530	375 375
165/70R13C 6PR	88/86S	5.00B	562	170	560/530	240 250
165/80R13	83T	4.50B	594	165	487 475	250 300
175/70R13	82T	5.00B	576	177	530 307	300 300
185/70R13	86T	5.00B	590	189	387 437	250 300
155/50R14	67T	5J	512	162	462 515	250 250
165/60R14	75H	5J	554	170	475 500	375 375
165/65R14	79H	5J	570	170	690/650	250 250
165/70R14	81T	5J	588	170	690/650	250 250
165/80R14	85T	4½J	620	165	475 530	250 300
175/65R14	82H	5J	584	177	560 530	300 300
175/70R14	84T	5J	602	177	615 560	300 300
175/70R14LT 6PR	95/93Q	5J	602	177	500 560	300 250
175/70R14C 6PR	95/93Q	5J	602	177	475 515	300 250
185/60R14	82H	5½J	578	189	560 615	300
185/65R14	86H	5½J	596	189	615 670	
185/70R14	88T	5½J	616	189	710	
195/60R14	86H	6J	590	201		
195/70R14	91T	6J	630	201		
205/60R14	88H	6J	602	209		
185/60R15	84H	5½J	603	189		
185/65R15	88H	5½J	621	189		
195/50R15	82H/V	6J	577	201		
195/55R15	85H/V	6J	595	201		
★ 195/60R15	88H	6J	615	201		
195/65R15	91H	6J	635	201		
205/60R15	91H/V	6J	627	209		
205/65R15	94H	6J	647	209		
215/65R15	96H	6½J	661	221		

UHP TIRE

Applicable Models



Product features:

- Excellent high speed handling.
- Excellent hydroplaning performance.
- Fuel economy, great wet grip and performance.
- Excellent ride and low noise driving experience.



CLASSIC CL13

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
205/45R16	87V XL	7J	590	206	545	340 340
205/50ZR17	93W XL	6½J	638	214	650	340 340
205/55ZR17	95W XL	6½J	658	214	690	300 300
235/55ZR17	103W XL	7½J	690	245	875	340 340
215/55R18	95V	7J	693	226	690	300
235/45ZR18	94W	8J	669	236	670	
★	98W XL	8J	669	236	750	
235/45ZR18	101W XL	7½J	693	245	825	
235/50ZR18	101W	7½J	741	245	825	


★ 235/55R19

AT TIRE

Applicable Models



CLASSIC CL14



Product features:

Upgraded material offers good handling and ride comfort.
Two steel belts and plies enhance carcass strength.
Splice-free belt hoops ensure tire strength and driving safety.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
175/80R14	88T	5J	636	177	560	300 350
LT215/75R14 6PR	98/95S	6J	678	216	750/690	300 300
205/60R15	91H 94H	6J	627	209	615 670	300 300
205/65R15	96T	6J	647	209	710 800	450 350
205/70R15	100T	6J	669	209	975/875	550
225/70R15	107/103S	6½J	697	228	1030	
225/70R15LT	109S	6½J	697	228	1180/1090	
31X10.50R15LT	114/111R	8½J	775	268		
31X10.50R15LT		8½J	775	268		


CLASSIC CL14

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
205/60R16	92H	6J	652	209	630 750	300 300
215/65R16	98T	6½J	686	221	800 950	300 300
235/60R16	100T	7J	688	240	975 1090	300 300
235/70R16	106T	7J	736	240	1120	300 550
245/70R16	107T	7J	750	248	1215/1120	550 550
255/70R16	111T	7½J	764	260	1215/1120	550 550
265/70R16	112T	8J	778	272	1380/1260	550 550
LT215/85R16	115/112R	6J	772	216	1380/1260	550 300
LT225/75R16	115/112R	6J	744	223	1380/1260	300 300
LT235/85R16	120/116R	6½J	806	235	1450/1320	300 300
LT245/70R16	120/116R	7J	750	248	1550/1400	550
LT245/75R16	120/116R	7J	774	248	1550/1400	
LT265/70R16	121/118R	8J	778	272	850 850	
LT265/70R16	123/120R	8J	778	272	900 1120	
LT265/75R16	123/120R	7½J	804	267	1215	
225/65R17	102T	6½J	724	228	1400/1285	
235/60R17	102T	7J	714	240		
235/65R17	104T	7J	738	240		
265/65R17	112T	8J	776	272		
265/70R17	115T	8J	804	272		
LT265/65R17	120/117R	8J	776	272		



CLASSIC CL15

LTR TIRE




Product features:

- 4 Main grooves & sipes ensure optimal grip on wet roads.
- Good performance on rain, snow, mud, and non-paved roads.
- Low rolling resistance compound offers excellent fuel economy.
- Low noise and more driving comfort.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
185/75R16C	104/102R	5J	684	184	900/850	475

AT TIRE

Applicable Models



Product features:

Good high speed performance on complicated road surface.

Wavy groove design grips onto various road surfaces effectively.

Randomized groove distribution reduces noise.

Multiple tread block sizes improve traction and comfort.



CLASSIC CL16

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
235/75R15C 6PR	104/101S	6½J	733	235	900/825	350 350
235/75R15LT 6PR	104/101S	6½J	733	235	900/825	550 550
235/75R15C 10PR	116/113S	6½J	733	235	1250/1150	
235/75R15LT 10PR	116/113S	6½J	733	235	1250/1150	


10PR

MT TIRE

Applicable Models



CLASSIC CL17



Product features:

Special tread compound tailored for MT application improves outstanding and tread wear.


Reinforced shoulder blocks and 3D sidewall improve pass-ability in harsh road.

Variable pitch design with large blocks improve grip and durability.

Size	LI/SS	Std. Rim	Overall Diameter (mm)	Section Width (mm)	Max Load (kg)	Inflated Pressure (kPa)
LT235/75R15	104/101Q	6½J	733	235	900/825	350 350
31X10.50R15LT	109Q	8½J	775	268	1030	550 550
LT235/85R16	120/116Q	6½J	806	235	1380/1260	550 350
LT245/75R16	120/116Q	7J	774	248	1380/1260	450 550
LT255/70R16	120/117Q	7½J	764	260	1400/1285	550 550
LT265/70R16	110/107Q	8J	778	272	1060/975	
LT265/70R16	117/114Q	8J	778	272	1285/1180	
LT265/75R16	123/120Q	7½J	804	267	1550/1400	
LT265/65R17	120/117Q	8J	776	272	1400/1285	
LT265/70R17	121/118Q	8J	804	272	1450/1320	

LTR TIRE

Applicable Models



MIX-200

SIZE	PR	STD RIM	LOAD INDEX/ SPEED RATING	MAX LOAD (kg/lbs)		INFLATED PRESSURE (kPa/psi)		TIRE DIMENSION (mm)	
				SINGLE	DUAL	SINGLE	DUAL	SW	OD
700R16C	12	5.50F	115/110 N	1150/2535	1120/2469	515/74	515/74	200	775
750R16C	14	6.00G	122/118 L	1405/3295	1315/2899	740/107	740/107	215	805